

CR LETSGO HIGH PERFORMANCE 90

| PROPERTIES | UNITS | TYPICAL VALUE |
|-----------------------------|------------------|---------------|
| BASISWEIGHT | g/m ² | 90 |
| CALIPER | µm | 117 |
| MOISTURE | % | 5,6 |
| COBB TOPSIDE | g/m ² | 100 |
| TENSILE STRENGTH MD | kg/15mm | 10 |
| TENSILE STRENGTH CD | kg/15mm | 4 |
| TEAR MACHINE DIRECTION | mN | 650 |
| ROUGHNESS BENDTSEN WIRESIDE | ml/min | 180 |
| SMOOTHNESS BEKK WIRESIDE | s | 30 |
| OPACITY | % | 93,5 |
| CIE WHITENESS | % | 160 |

PRODUCT AND ENVIRONMENTAL FACTS

| | |
|--------------------|---|
| Raw materials | <ul style="list-style-type: none"> - Primary fibres from sustainable forestry - 100% chemical fibres - ECF bleached - Recoverable fibres and fillers |
| Production process | <ul style="list-style-type: none"> - Production process in accordance with Dutch environmental laws and regulations - Quality assurance according to ISO 9001 - Environmental assurance according to ISO 14001 |
| Health and safety | <ul style="list-style-type: none"> - Contact with dry and fatty foods according to BfR Empfehlung 36. - Heavy metal migration and content according to <ul style="list-style-type: none"> * European safety of toys EN 71/3:1994 D (BS EN 71/3 1995) * Children Toys Protection Act (CTPA) - ASTM F-963-86 * Confederation of North Eastern Governors (CONEG) |

Valid from :

20-11-2018

Ref: 170200090

The present product profile indicates the typical properties of the described papergrade. It does not represent a binding product specification.

The latest issue of this product profile is available on request.